



Roof Consultants

The Roof Centre Ltd.

Unit 45 Finglas Business Centre, Jamestown Road, Dublin 11
Phone: 01 834 1001 Fax: 01 834 1050 Email: info@theroofcentre.com

Technical Roof Consultants & Suppliers of High Performance Waterproofing Systems



Armourfix 20 F-20



APPLICATION: Mechanically Fastened Base Sheet

COMPOSITION:

Top Coating: APP modified Bitumen

Inlay: Polyester Fleece

Bottom Coating:



FINISHING:

Top Side: Foil

Bottom Side: Naked Unsaturated Polyester

DIMENSIONS:

Length: 20 x 1 Metre

Weight Per Roll: 28 KG

Thickness: 2 mm

Rolls Per Pallet: 20

TECHNICAL INFORMATION:

	<i>Tensile Strength</i>		<i>Elongation @ Break</i>		<i>Tear Strength</i>	
	<i>Length</i>	<i>Width</i>	<i>Length</i>	<i>Width</i>	<i>Length</i>	<i>Width</i>
<i>Typical</i>	621 N	457 N	>= 20%	>= 20%	>= 70 N	>= 70 N
<i>Test</i>	<i>EN 12311-1</i>		<i>EN 12311-1</i>		<i>EN 12310-1</i>	

	<i>Nail Tear</i>	<i>Heat Resistance</i>	<i>Dimensional Stability</i>	<i>Cold Bend Temperature</i>
<i>Typical</i>	175 N	130 °C		-17.5 °C
<i>Test</i>	<i>EN 12310-1</i>	<i>EN 1110</i>		<i>EN 1109</i>