




CLASSIC SHINGLES



Top quality fibreglass high grade bitumen shingle

YOUR BENEFITS

- The most time-tested and widely used shingle
- Exceptional value for money
- Covered by an IKO quality guarantee
- Highly resistant to colour fading



	Superglass®-3 Tab	Superglass®-Biber
Length (EN 544)	1000 mm (+/- 3)	1000 mm (+/- 3)
Width (EN 544)	336 mm (+/- 3)	336 mm (+/- 3)
Weight (slope > 25°)	+/- 9,6kg/m ²	+/- 10,1 kg/m ²
Coverage/bundle	3 m ²	3 m ²
Shingles/bundle	21	23
Bundles/pallet	51	51
Granule adhesion (EN 12039)	max. 1,2 g	max. 1,2 g
Tensile length* (EN 12311-1)	900 N/50 mm	900 N/50 mm
Tensile width* (EN 12311-1)	600 N/50 mm	600 N/50 mm
Elongation length* (EN 12311-1)	3,50 %	3,50 %
Elongation width* (EN 12311-1)	3,50 %	3,50 %
Nail tear resistance* (EN 12310-1)	140 N	140 N
Fire resistance	DIN 4102/7 MSZ 14800-11 ZP-2/1991	DIN 4102/7 MSZ. 14800-11 ZP-2/1991

* Registered average values.

Notice: The information is subject to change without prior notice. Consult our shingle overview leaflet or website www.iko-shingles.eu for colour availability of the products.