



Roof Consultants

The Roof Centre Ltd.

Unit 45 Finglas Business Centre, Jamestown Road, Dublin 11
Phone: 01 834 1001 Fax: 01 834 1050 Email: info@theroofcentre.com

Technical Roof Consultants & Suppliers of High Performance Waterproofing Systems



Glassgum 3/10m



APPLICATION: Base sheet/Vapour Barrier - Torch Bonded

COMPOSITION:

Top Coating: TPO / APP modified bitumen
Inlay: Glassfibre Reinforcement 60 g/m²
Bottom Coating: TPO / APP modified bitumen

DEFINITIONS: **TPO - Thermo Plastic Olefin**
- Adds rigidity, compound elongation & flexibility, increases temperature and UV Resistance

APP - Atactic Polypropylene
- Adds flexibility, increases temperature and UV Resistance

FINISHING:

Top Side: Sand / Talc
Bottom Side: Thermofusible Foil

DIMENSIONS:

Length: 10 x 1 Metre *Weight Per Roll:* 36 KG
Thickness: 3 mm *Rolls Per Pallet:* 25

TECHNICAL INFORMATION:

	<i>Tensile Strength</i>		<i>Elongation @ Break</i>	
	<i>Length</i>	<i>Width</i>	<i>Length</i>	<i>Width</i>
<i>Typical</i>	400 ± 10%	300 ± 10%	2.5% ± 10%	2.5% ± 10%
<i>Test</i>	<i>EN 12311-1</i>		<i>EN 12311-1</i>	

	<i>Heat Resistance</i>	<i>Cold Bend Temperature</i>
	<i>Typical</i>	130 ± 10%
<i>Test</i>	<i>EN 1110</i>	<i>EN 1109</i>