



Roof Consultants

The Roof Centre Ltd.

Unit 45 Finglas Business Centre, Jamestown Road, Dublin 11
Phone: 01 834 1001 Fax: 01 834 1050 Email: info@theroofcentre.com

Technical Roof Consultants & Suppliers of High Performance Waterproofing Systems



Anti Root 4 T Mec 180 WW 7.5 m



APPLICATION: Top Sheet - Fully Torch Bonded

COMPOSITION:

Top Coating: APP modified bitumen with Root Rejecting Element

Inlay: Non-woven Polyester 180 g/m²

Bottom Coating: APP modified bitumen with Root Rejecting Element



DEFINITIONS: **Root Rejecting Element**

- 4 year period FLL German Root Test Accomplished

APP - Atactic Polypropylene

- Adds Dimensional Stability, increases temperature and UV Resistance

FINISHING:

Top Side: Sand / Talc

Bottom Side: Thermofusible Foil

DIMENSIONS:

<i>Length:</i>	7.5 x 1 Metre	<i>Weight Per Roll:</i>	36 KG
<i>Thickness:</i>	4 mm	<i>Rolls Per Pallet:</i>	20

TECHNICAL INFORMATION:

	<i>Tensile Strength</i>		<i>Elongation @ Break</i>	
	<i>Length</i>	<i>Width</i>	<i>Length</i>	<i>Width</i>
<i>Typical</i>	760 N ± 10%	480 N ± 10%	40% ± 10%	50% ± 10%
<i>Test</i>	<i>EN 12311-1</i>		<i>EN 12311-1</i>	

	<i>Nail Tear</i>	<i>Heat Resistance</i>	<i>Dimensional Stability</i>	<i>Cold Bend Temperature</i>
<i>Typical</i>	135 N ± 10%	145 °C ± 10%	0.30%	- 15 °C ± 10%
<i>Test</i>	<i>EN 12310-1</i>	<i>EN 1110</i>	<i>EN 1107-1</i>	<i>EN 1109</i>