The Roof Centre Ltd.

Unit 45 Finglas Business Centre, Jamestown Road, Dublin 11
Phone: 01 834 1001 Fax: 01 834 1050 Email: info@theroofcentre.com

Technical Roof Consultants & Suppliers of High Performance Waterproofing Systems

Glassgum 2/15m

APPLICATION: Vapour Control or Base Sheet - Full or Partial Torch Bonded

COMPOSITION:

Top Coating: TPO / APP modified bitumen
Inlay: Glassfibre Reinforcement 60 g/m2
Bottom Coating: TPO / APP modified bitumen

DEFINITIONS: **TPO - Thermo Plastic Olefin**
- Adds rigidity, compound elongation & flexibility, increases temperature and UV Resistance

APP - Atactic Polypropylene
- Adds flexibility, increases temperature and UV Resistance

FINISHING:

Top Side: **Sand / Talc**
Bottom Side: Thermofusible Foil

DIMENSIONS:

Length:	15 x 1 Metre	*Weight Per Roll:*	36 KG
Thickness:	2 mm	*Rolls Per Pallet:*	20

TECHNICAL INFORMATION:

	Tensile Strength		***Elongation @ Break***	
	Length	*Width*	*Length*	*Width*
Typical	400 ± 10%	300 ± 10%	2.5% ± 10%	2.5% ± 10%
Test	***EN 12311-1***		***EN 12311-1***	

	Heat Resistance	***Cold Bend Temperature***
Typical	130 ± 10%	-7.5 ± 10%
Test	***EN 1110***	***EN 1109***