






# HIGH-END TRADITIONAL SHINGLES



Superior quality fibreglass high grade bitumen shingle

## YOUR BENEFITS

- Exceeds by far most severe worldwide standards
- Thicker glassfibre inlay
- Higher bitumen content
- Available in many shapes and colours



	Armourglass®	Victorian®	Diamant®
Length (EN 544)	1000 mm (+/- 3)	1000 mm (+/- 3)	1000 mm (+/- 3)
Width (EN 544)	336 mm (+/- 3)	336 mm (+/- 3)	284 mm (+/- 3)
Weight (slope > 25°)	+/- 10,9 kg/m <sup>2</sup>	+/- 11,5 kg/m <sup>2</sup>	+/- 10,5 kg/m <sup>2</sup>
Coverage/bundle	3 m <sup>2</sup>	2,75 m <sup>2</sup>	3 m <sup>2</sup>
Shingles/bundle	21	21	27
Bundles/pallet	48	48	42
Granule adhesion (EN 12039)	max. 1,2 g	max. 1,2 g	max. 1,2 g
Tensile length* (EN 12311-1)	1000 N/50 mm	1000 N/50 mm	1000 N/50 mm
Tensile width* (EN 12311-1)	700 N/50 mm	700 N/50 mm	700 N/50 mm
Elongation length* (EN 12311-1)	3,00 %	3,00 %	3,50 %
Elongation width* (EN 12311-1)	3,00 %	3,00 %	3,50 %
Nail tear resistance* (EN 12310-1)	160 N	160 N	160 N
Fire resistance	DIN 4102/7 PN-B-02872/1996 MSZ 14800-11 Önorm B 3800/3 BS 476/3 M3 ZP-2/1991 EN ISO 11925-2	DIN 4102/7 PN-B-02872/1996 MSZ 14800-11	DIN 4102/7 PN-B-02872/1996 MSZ 14800-11 Önorm B 3800/3

\* Registered average values.

**Notice:** The information is subject to change without prior notice. Consult our shingle overview leaflet or website [www.iko-shingles.eu](http://www.iko-shingles.eu) for colour availability of the products.